















Somany Ceramics Limited: Noida: F-36, Sector-6; Ph.: 0120-4627900.

Ahmedabad: 601 to 606, 6th floor, Aalps Euphoria, Opp. Adani CNG Pump, B/s. Gota Flyover, S. G, Highway, Ahmedabad- 382481, Ph.: 079-27661103 & 04 Registered office: 2, Red Cross Place, Kolkata - 700001; Ph.(033) 22487406/5913 www.somanyceramics.com I e-mail marketing@somanyceramics.com

**Toll Free No. 1800-103-0004** (Timing-10:00am to 6:30pm; Mon-Fri)











GET IT ON Google play







#### THE PERFECT SOLUTION FOR YOUR OUTDOOR NEEDS

Elevate your outdoor spaces with our exquisite 400x400mm Durastone tiles, perfectly complementing sandstone ochre. These tiles redefine outdoor elegance, blending stunning design with precision craftsmanship. Their versatility ensures they enhance various settings, creating a captivating outdoor ambiance. Explore endless possibilities here, embracing the finest essence of the outdoors with Durastone.

#### **KEY FEATURES**



Anti Skid





High Flexural Strength



Easy To Clean



Suitable For Indoor & Outdoor Application



High Mechanical Resistance



Floor Tiles



Chromatic Properties





Heavy Load Bearing

Eco Friendly & Recyclable



Fire Resistance



Chemical Resistance



Thickness

#### **APPLICATION AREA**



Wear Resistance



Exit Area



Industrial Area



Metro



Gazebos














Size - **400x400mm** 

Surface - **Matt** 

















ALVA BROWN





ALVA GREY





AISHA BROWN





Size - **400x400mm** 

Surface - Matt

ARIN BEIGE






















EBRAR BEIGE









ELIA GRIS



ELIA BROWN







Size - **400x400mm** Surface - **Matt**  40x 40cm


















EDDIE GRIS



















DURASTONE HEAVY DUTY VITRIFIED TILES

Size - **400x400mm** Surface - **Matt** 

LIMES BROWN


40x 40cm



















LIMES GREY














Size - **400x400mm** 


Surface - Matt

MAGNET GREY


40x 40cm




















NARVE GREY









RODIN GRIS



**RODIN GREY** 



#### TECHNICAL SPECIFICATION










## **DESIGN, PATTERN & SHADE VARIATION GUIDE**


Current development efforts have made ceramic tiles to resemble and look authentically identical to natural material (Stone, Wood, Fabric), and it has become increasingly difficult in many cases, to distinguish between two.

Recognising this situation, it is necessary to be informed on the grade of design & pattern variation that is expected from these products. As a general reference, the design & Pattern guide below classifies a scale of ranges according to the degree of variation.









**V1** Uniform Appearance

Slight Variation

**V3** Moderate Variation

V4 Substantial Variation

The classification is as follow:

✓ Minimal Variation

✓≥ Slight Variation

**V** Random Variation

▼4 Substantial Variation



High Definition Image


While laying the tiles please follow the arrow on the back of the tiles. For removing the wax from the surface of the tiles please use the soft cotton cloth for rubbing with any boric/talk powder. And use with spacer to look good

PACKAGING DETAIL FOR DURASTONE TILES - 400X400MM							
Nominal Size	Thickness	Avg. Wt. Per Box (Kg.)	No. of Tiles Per Box	Coverage Area Per Box			
400x400MM (Digital Pavesmart)	11.5mm	19.5 kg	5	0.80 sq meter / 8.61sq feet			

TECHNICAL SPECIFICATION FOR DURASTONE TILES - 400X400MM						
Characteristics	Requirement as per ISO 13006:2018 ≤ 0.5% Group B I a	Requirement as per IS 15622:2017 0.08≤E≤3.0 Group Blb	Our value	Test Method		
Dimension & Surface Quality						
Length & Width	± 0.3%	± 0.1%	± 0.10%			
Thickness	± 5.0%	± 5.0%	± 4.0%			
Straightness of Side	± 0.30%	± 0.10%	± 0.10%			
Rectengularity	± 0.30%	± 0.10%	± 0.10%			
Surface Flatness				IS 13630 Part 1/		
Center curvature (%) ( max.Deviation)	± 0.40%	± 0.50%	± 0.2%	ISO 10545-2		
Edge curvature (%) ( max.Deviation)	± 0.40%	± 0.50%	± 0.2%			
Corner warpage (%)( max.Deviation)	± 0.40%	± 0.50%	± 0.2%			
Surface Quality	Min. 95 % of tiles will be	Min. 95 % of tiles will be	Min. 95 % of tiles will be			
	free from visible defects	free from visible defects	free from visible defects			
Physical Properties		'				
Water Absorption	Avg. 0.5 %,	Avg. 0.08 ≤ E ≤ 3.0	Av < 3.0 %	IS 13630 Part 2/		
	Individual 0.6% max			ISO 10545-3		
Modulus of Rupture [N/mm²]	Av 35, Individual 32 min	Av 30, Individual 27 min	Avg.> 35 Min. 1800 N	IS 13630 Part 6/ISO 10545-4		
Breaking Strength in N	1300 N	1100 N				
Moisture Expansion in mm/m	Test Method Available	0.02 Max	Max,0.02	IS 13630 Part 3/ISO-10545-10		
Scratch Hardness of surface (Mohs)	N/A	Min. 5	Min-6	IS 13630 Part-13		
Resistance to Surface Abrasion of Glaze Tiles	Min Class II	Min II	Gr IV	IS 13630 Part 11/ ISO 10545-Part 7		
Coefficient of linear thermal expansion from embiant temperature to 100° C	Test Method Available	Max 7 X 10 -6 K-1	Max 6 X 10 -6 K-1	IS 13630 Part 4/ ISO 10545-8		
Thermal Shock Resistance	Required	Min 10 Cycle Passed	10 cycle passed	IS 13630 Part 5/ISO-10545-9		
Crazing Resistance	N/A	Min 4 Cycles @ 7.5 bar, Min.	4 cycle passed	IS 13630 Part 9/ISO 10545-11		
Imapct Resistance as Co-efficient of Restitution (COR)	Test Method Available	Min 0.55	Min 0.55	IS 13630 Part 5/ISO-10545-14		
Frost Resistance	Required	Required if agreed	100 Cycle Passed	IS 13630 Part 10/ISO 10545-12		
Chemical Resistance (glazed Tiles)						
Stain Resistance	Min Class 3	Min Class 1	Min Class 2	IS 13630 Part 8/ISO 10545-14		
Resistance to household chemicals	Minimum B	Required if agreed	Min Class AA			
Resistance to acids and alkalis (with exception of hydrofluoric acid and its compounds)	Declared Value <sup>f</sup>	Required if agreed	Min Class AA	IS 13630 Part 8/ISO 10545-14		

The reproduction of tiles in this catalogue is restricted to four color printing only and tiles are not in relative sizes, therefore customers are advised to see the physical sample before placing the order. "Technical Specification" for Somany wall & floor tiles are applicable only for premium quality tiles. Please inspect all tiles prior to installation. Company will not entertain complaints once tiles are laid/fixed. Complaints will not be entertained for Borders, Highlighters & Motifs.

21 20



# Ezy Fix

SOMANY

TILES ADHESIVES & GROUTS



# HIGH STRENGTH POLYMER MODIFIED

TILE ADHESIVE



#### BENEFITS

- » READY AND EASY TO USE
- » EXCELLENT BONDING WITH ALL SURFACES
- FAST SETTING
- SELF-CURING

#### USES **(**

- FOR FIXING ALL TYPE OF TILES
- FOR NEW FLOORING AND RENOVATION
- » CAN BE USED FOR TILE ON TILE